

ROTARY ENGINE OIL 10W-30 FULL SYNTHETIC

IDEMITSU RACING

This formulation has been specifically engineered to meet the unique requirements of a rotary engine. The technology base for this formulation goes back to the first & only 24 Le Mans race winner using a rotary engine for which IDEMITSU developed the winning oil.

- Allows for Better Sealing of the Chamber, Facilitating More Power Generation
- Extends the Life of Turbochargers by Reducing Bearing Coking
- Minimizes Exhaust Port Clogging
- Superior Shear Stability
- Exceptional Wear Protection & Durability to Protect Main Bearing and Eccentric Shaft
- Contains Special Molybdenum Agents to Reduce Friction, Which Increases Horsepower & Torque

Application:

Formulated Specifically For High Performance Rotary Engines

Compatible with Methanol Alcohol and Gasoline Fuel

Fill Crankcase to Manufacturer's Recommended Level

Characteristics:

Exceeds API Service Class SL

SAE Grade: 10W-30 64.6 cSt Viscosity @ 40°C

> 10.5 cSt @ 100°C 152

Viscosity Index: CCS Viscosity @ -15°C 2,090

@ -20°C 3,420

-54°C Pour Point: 250°C Flash Point:

Packaging:

Quart (.946 L)

IDEMITSU Racing USA

www.idemitsu-usa.com

Manufactured & Distributed by Apollo America Corporation

Headquarters: 701 Port Rd., 2041 Rosecrans Ave., Suite 355 Jeffersonville, IN 47130

El Segundo, CA (310) 563-1930

Sales:

sales@idemitsu-usa.com

